



# INSULATION & PACKAGING DISTRIBUTORS CC

## FABUFILL

Fabufill is SABS and Tiasa accredited. It is 100% eco-friendly. It is made from recycled PET bottles and fully recyclable. It is 100% people friendly. It comes in simple and safe, easy to install rolls. It is non-allergenic, non-irritant and flexible. No special health and safety precautions are required when installing Fabufill. It will not absorb water and will dry naturally should it be exposed to small amounts of water.

Fabufill has been fire tested and is safe to use in both residential and commercial applications. It will not contribute to the spread of flame and the product will self-extinguish once the heat source is removed. Fabufill has a type 1 classification.

Fabufill is non-toxic. There are no chemical additives and is completely odourless. It is maintenance free. It retains loft and does not degrade over time.

Easy to install. All you need is a measuring tape, scissors and a balancing plank. Measure distance between roof beams, roll out onto ceiling board (make sure there are no gaps). When desired area is covered, cut or tear. It is advised to lay the material under any wiring and to cut around down lights

The standard width of Fabufill is 1200mm, we can however manufacture 750mm to accommodate the client's requirements. The density of the material is 10.1kg/m<sup>3</sup> which provide residential and commercial properties with the perfect temperatures during both winter and summer.

Fabufill's thermal resistance, also known as the "R"-value for the different sizes are as follows:

Thickness (mm)	Dimensions (mm)	R Value M <sup>2</sup> k/w
40mm	10000x1200x40	0.94
50mm	10000x1200x50	1.15
75mm	8000x1200x75	1.69
100mm	6000 x 1200 x 100	2.20

(SABS testing concluded and accredited)

<http://www.tiasa.org.za/http://www.tiasa.org.za/>